



TIMBERWOLF®
LEAD THE PACK

Timberwolf's range of road towable hydraulic wood chippers are our most popular 'all round' choice. The versatility means they can be used effectively across a range of applications and conditions including landscaping, tree surgery and contract work.

TW 230HB

LIGHTWEIGHT AND POWERFUL



PETROL OR DIESEL CHOICE:

Renowned for its superior performance, reliability, longevity and easy servicing, the TW 230HB range is available with either a high-power Briggs and Stratton Vanguard EFI V-twin petrol engine or high torque Kubota 4-cylinder diesel engine.

www.timberwolf-uk.com



TIMBERWOLF®

LEAD THE PACK

FEATURES AND BENEFITS:

Lightweight, powerful, and reliable, the TW 230HB range is the best in class:

- 24.8 hp Kubota diesel or 40 hp B&S Vanguard EFI V-Twin petrol engine options
- Class-leading 230 mm x 160 mm infeed opening (6 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- Sub 750 KG – Lightweight and manoeuvrable
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- 3-year warranty as standard with optional 5-year extended warranty
- Timberwolf - easy to use, easy to own

TW 230HB PETROL SPECIFICATIONS

PETROL ENGINE

40 hp B&S Vanguard EFI-V Twin

Fuel tank capacity	18 litres
--------------------	-----------

DIMENSIONS

Weight	672 kg
--------	--------

Height	2182 mm
--------	---------

Height with discharge tube removed	1539 mm
------------------------------------	---------

Length (tray down)	3568 mm
--------------------	---------

Length (tray up)	3047 mm
------------------	---------

Width	1519 mm
-------	---------

CHIPPING FEATURES

Feed method	Twin hydraulic rollers c/w Auto Feed Control
-------------	--

Maximum diameter infeed	160 mm (6 ¼")
-------------------------	---------------

Discharge tube	280° adjustable discharge
----------------	---------------------------

Blades	2 x 135 mm double sided, fully hardened
--------	---

TW 230HB DIESEL SPECIFICATIONS

DIESEL ENGINE

24.8 hp Kubota

Fuel tank capacity	18 litres
--------------------	-----------

DIMENSIONS

Weight	747 kg
--------	--------

Height	2162 mm
--------	---------

Height with discharge tube removed	1516 mm
------------------------------------	---------

Length (tray down)	3800 mm
--------------------	---------

Length (tray up)	3297 mm
------------------	---------

Width	1518 mm
-------	---------

CHIPPING FEATURES

Feed method	Twin hydraulic rollers c/w Auto Feed Control
-------------	--

Maximum diameter infeed	160 mm (6 ¼")
-------------------------	---------------

Discharge tube	280° adjustable discharge
----------------	---------------------------

Blades	2 x 135 mm double sided, fully hardened
--------	---